

**IN THE CLAIMS:**

1. (Currently Amended) A reactor unit comprising:  
a basket body which has one open face and which is made of a metal;  
a plurality of reactor bodies which are accommodated in the basket body;  
a lid body which is made of a metal, which closes the open face of the basket body, and in which outlet holes are formed; and  
a mold resin which is a curable resin and with which the basket body is completely filled with a coil of each of the reactor bodies having been drawn out from a corresponding one of the outlet holes of the lid body,  
~~wherein at least one a partition, which is located between the reactor bodies and whose leading end~~ extends from an inner face of at least one of the basket body and the lid body, and an entire surface of a leading end of the partition contacts ~~on~~ an inner face of the other, ~~is formed protrusively when the open face of the basket body is closed by the lid body.~~
2. (Previously Presented) The reactor unit according to claim 1, wherein the at least one partition is formed integrally with at least one of the basket body and the lid body.
3. (Previously Presented) The reactor unit according to claim 1, wherein the at least one partition is so formed as to extend an entire depth of, as well as substantially across an entire width of, the basket body.
4. (Original) The reactor unit according to claim 3, wherein an opening through which the mold resin passes is formed in a certain part of the partition.
5. (Original) The reactor unit according to claim 4, wherein the opening is formed in the vicinity of the inner face of the lid body.

6. (Original) The reactor unit according to claim 5, wherein  
the opening is a notch in which a wire for a temperature detector disposed in the  
basket body is located.
7. (Previously Presented) The reactor unit according to claim 1, wherein  
there is a gap between the at least one partition and the reactor bodies while the  
mold resin is interposed therebetween.
8. (Previously Presented) The reactor unit according to claim 1, wherein  
there is no gap between the at least one partition and the reactor bodies while the  
mold resin is interposed therebetween.
9. (New) The reactor unit according to claim 2, wherein the partition is formed  
integrally with the basket body.
10. (New) The reactor unit according to claim 2, wherein the partition is formed  
integrally with the lid body.